

Aluminium Bi-Folding Doors

Enquiry Form

Your Details

I am a Homeowner Trade Customer

Name

Company

Address

Post Code

Tel/Mobile

Email

Project Details

Collect Deliver Required Date (week)

Delivery Address

Post Code

Delivery Contact

Delivery Telephone

Customer Ref

Customer Order No

Project Type: New build Refurbishment

Please note, windows and doors are subject to Building Regulations. The regulations changed in 2022 and it's the installer's responsibility to ensure the products are compliant for their intended use where they're installed. Use our specification tool available at www.quickslide.co.uk/requirement-calculators/ to help you understand the product specification required to comply.

Door Specification

Quantity

Location


Width

Oversized Width (>1000mm)

Height

Door Configuration Code

Illustration (viewed externally)



Sliding Direction (viewed externally)

- From the left
 From the right

Door Opens

- Inwards
 Outwards

Threshold

- Standard 50mm
 Low threshold 20mm
 Low threshold w. ramp 20mm

Door Colour External

- White
 Grey
 Black

NEW WOODGRAIN FINISHES

- White Woodgrain
 Cream Woodgrain
 Agate Grey Woodgrain
 Chartwell Green Woodgrain
 Anthracite Grey Woodgrain
 Black Woodgrain
 Irish Oak
 Golden Oak
 Rosewood

Door Colour Internal

- White
 To Match External

Trickle Vents

You have the option of a flush vent fitted into the head of the sash or link vent which requires a 42mm add-on above the outer door frame. Please note trickle vents cannot be retro-fitted.

- Flush Vent, 2057 EA per vent
 Link Vent, 5000 EA per vent
 42m Add-on Required
 Trickle Vents not required

Handle Colour

- White
 Black
 Chrome
 Anthracite Grey
 Satin Chrome

Magnetic Door Catch

- White
 Black
 Chrome
 Anthracite Grey
 Satin Chrome

PAS 24 Security Upgrade

Laminated glass also required

90° Restrictors

Sill

On woodgrain doors, 150mm sill only

- No sill
 85mm
 150mm
 190mm
 225mm

Glazing

Glazed options come with Argon Gas and Toughened Glass as standard

- Unglazed
 Double Glazed
 1.6W/m²K / °C DSER
 Double Glazed, Laminated
 1.6W/m²K / °C DSER
 Triple Glazed
 1.3W/m²K
 Triple Glazed, Laminated
 1.4W/m²K

Glazing with Integral Blinds

- Double Glazed, Integral Blinds
 1.6W/m²K / °C DSER
 Double Glazed, Laminated,
 Integral Blinds 1.6W/m²K / °C DSER

Colour of outer casing:

Colour of blinds:

Obscure Glass

In addition to glazed option

- Satin
 Stipple
 Other:

Spacer Bar Colour


- White
 Grey
 Black

Frame Extenders (Add-ons)

- 20mm
 42mm (required with Link Vent)
 Left
 Right
 Top
 Bottom
 Midrail (white/grey only)


Sash Options

- Curved Sash




Square Sash

Longer lead time applies




Threshold Options


Standard Threshold



Low Threshold



Low Threshold with Ramp



Comments:

Tel: 0844 5610 623 | Fax: 0844 5610 624

Email: sales@quickslide.co.uk

Heaton Estate, Bradford Road, Brighouse, West Yorkshire, HD6 4BW